

Horn IP Speaker 15W

IPS302015-S



Features

- Built in 1 high-quality speaker with loud sound, long penetration and clear
 - Support alarm broadcast with uniview NVR, video and audio linkage.
 - Built in storage, support uploading custom audios
 - Support two-way audio
 - Support PoE power supply
-

Specifications

Model	IPS302015-S
Speaker	
Rated Power	15 W
Max. Acoustic Pressure	122 dB SPL
Frequency Response	300 Hz to 12.5 kHz
Impedance	8 Ω
Material	
Material	ABS Plastic
Network	
Network Protocol	IPv4, HTTP, HTTPS, DNS, SSL/TLS, TCP, UDP, DHCP, UPnP, ARP, SSH
Interface Protocol (API)	ONVIF, RTSP, RTP, LAPI
Browser	Windows: Firefox (version 87 and above), Chrome (version 90 and above), Edge (version 90 and above) ; MAC: Safari (version 17 and above)
Build in Mic	
Amount	1
Frequency Response	100 Hz to 8 kHz
Sensitivity	-37 dBV/Pa
Sampling Rate	8 kHz
Quantization Bits	16 bit
Audio	
Broadcast	Regular Broadcast, Live Broadcast, Alarm Broadcast
Two-Way Audio	Support
Audio Compression	G.711U
Audio File Format	MP3, WAV
Audio File Size	2 KB \leq Audio File Size \leq 10 MB
Audio File Storage	64 MB
Audio File Number	100 (Include system built-in files)
Language	
Language	38 languages: Simplified Chinese, Traditional Chinese, English, Vietnamese, Thai, Turkish, Spanish (Latin America), Portuguese (Brazil), Spanish, Portuguese, French, German, Italian, Dutch, Polish, Czech, Hungarian, Slovak, Russian, Hebrew, Arabic, Ukrainian, Estonian, Bulgarian, Greek, Romanian, Danish, Swedish, Norwegian, Finnish, Croatian, Slovenia, Serbia, Korean, Japanese, Latvian, Lithuanian, Persian
Interface	
Network Interface	1 RJ45 10 M/100 M self adaptive Ethernet Interface
Audio In	1, RCA
Alarm In	2
Power Supply	PoE (IEEE 802.3af), DC 12 V/1.4 A
Working Environment	
Working Temperature	-30 $^{\circ}$ C to 55 $^{\circ}$ C (-22 $^{\circ}$ F to 131 $^{\circ}$ F)

Working Humidity	≤ 90% RH (non-condensing)
Dimensions	
Dimensions	220mm × 163mm × 235mm (8.7"×6.4"×9.3")
Approval	
Protection	IP66

Cable Interface

